

Direct Routing IIS

Configure wan/lan interface to allow receive

Change bond 101 to whatever you nic name is, use "**netsh interface ipv4 show interfaces**" to display names

```
PS C:\Users\Administrator> netsh interface ipv4 set interface "bond0" weakhostreceive=enabled
PS C:\Users\Administrator> netsh interface ipv4 set interface "bond0 - VLAN 101"
weakhostreceive=enabled
PS C:\Users\Administrator> netsh interface ipv4 set interface "bond0 - VLAN 102"
weakhostreceive=enabled
PS C:\Users\Administrator> netsh interface ipv4 set interface "Loopback Pseudo-Interface 1"
weakhostreceive=enabled
PS C:\Users\Administrator> netsh interface ipv4 set interface "Loopback Pseudo-Interface 1"
weakhostsendsend=enabled
```

```
PS C:\Users\Administrator> netsh interface ipv4 show interfaces
```

“ Idx Met MTU State Name

1 50 4294967295 connected Loopback Pseudo-Interface 1

3 15 1500 connected bond0

8 15 1500 connected bond0 - VLAN 101

7 15 1500 connected bond0 - VLAN 102

Add WAN IP to loopback interface, replace <VIP-WAN> for the interface IP

```
PS C:\Users\Administrator> netsh interface ip set address "Loopback Pseudo-Interface 1" static
<VIP-WAN> 255.255.255.255
PS C:\Users\Administrator> netsh interface ipv4 add address "Loopback Pseudo-Interface 1"
127.0.0.1 255.0.0.0
```

```
PS C:\Users\Administrator> Get-NetIPInterface
```

```
ifIndex InterfaceAlias AddressFamily NIMtu(Bytes) InterfaceMetric Dhcp
ConnectionState PolicyStore
-----
7 bond0 - VLAN 101 IPv4 1500 15 Disabled Connected ActiveStore
8 bond0 - VLAN 102 IPv4 1500 15 Disabled Connected ActiveStore
3 bond0 IPv4 1500 15 Enabled Connected ActiveStore
1 Loopback Pseudo-Interface 1 IPv4 4294967295 50 Disabled Connected
ActiveStore
```

Replace "1" for the ID of the loopback in your output

```
Set-NetIPInterface -InterfaceIndex 1 -InterfaceMetric 254
```

```
PS C:\Users\Administrator> netsh interface ipv4 show config
```

Your config showed look like below

```
“ Configuration for interface "Loopback Pseudo-Interface 1"
DHCP enabled: No
IP Address: <VIP-WAN>
Subnet Prefix: <VIP-WAN>/32 (mask 255.255.255.255)
IP Address: 127.0.0.1
Subnet Prefix: 127.0.0.0/8 (mask 255.0.0.0)
InterfaceMetric: 50
Statically Configured DNS Servers: None
Register with which suffix: Primary only
Statically Configured WINS Servers: None
```

Revision #4

Created 2019-07-31 04:06:17 UTC by Dave

Updated 2019-08-05 22:02:41 UTC by Dave